



Custom Work Deserves a Custom Bond

MSDS: **MPA FAST**

Read and understand this before using or handling product.

For emergency purposes: CP Industries (Chemtrec four letter ID: PLOT)

Chemtrec Emergency phone: 800-424-9300

Chemical description: Vinyl/ Acrylic Emulsion

General product use: Specialty Adhesive

For product information or purchasing:

CHEMICAL HAZARD RATING

Health=1 (slight) Fire=0 (least) Reactivity=0 (least)

Section One--Hazardous Ingredients

None known

Section Two--Physical Data

- Appearance and odor: White opaque liquid, with slight acetic odor.
- Storage life: 6 months @ 21C (70F)
- PH @ 25C: ~4.5
- Content of Volatile Organics (VOC) 35 gms/litre less water
- Boiling Point: 105C
- Evaporation Rate: As water, <1
- Flash Point: Not applicable
- Freezing Point: <0C
- Autoignition Temperature: Not applicable
- Lower explosion limit: Not applicable
- Percent volatile by weight: 45% @ 105C
- Solubility in water: miscible
- Specific Gravity: ~1.1
- Upper Explosion Limit: Not applicable
- Vapor Density: .62 (water) air=1
- Vapor Pressure: 17.5 MM HG @ 20C



Custom Work Deserves a Custom Bond

Section Three--Immediate Health Hazards

- **Skin absorption:** No hazards known.
- **Ingestion:** No hazards known.
- **Inhalation:** Not expected to be harmful under normal conditions of use. However, if allowed to become airborne, may cause irritation of nose, throat and lungs.
- **Skin:** May cause irritation on prolonged or repeated contact.
- **Eyes:** May cause irritation on prolonged or repeated contact.

Section Four--Emergency and First Aid procedures

- **Ingestion:** If accidentally swallowed dilute by drinking large quantities of water. Immediately contact poison control center or hospital emergency room for any other additional treatment directions.
- **Inhalation:** Remove to fresh air.
- **Skin contact:** In case of irritation, flush with water.
- **Eye contact:** Immediately flush eyes with plenty of water. Call a physician if irritation persists.

Section Five--Fire and Explosion Hazards

Will not burn. In case of fire use water spray, dry chemical, foam or CO₂. Use water to keep fire-exposed containers cool.



Custom Work Deserves a Custom Bond

Section Six--Safe Handling and Personal Protection

- **Personal protection**

Where air contaminants can exceed acceptable criteria, use NIOSH/MSHA approved respiratory protection equipment. Respirators should be selected based on the form and concentration of contaminants in air in accordance with OSHA 29 CFR 1910.134 or other applicable standards or guidelines.

If airborne contaminants are generated when the material is heated or handled, sufficient ventilation in volume and air flow patterns should be provided to keep air contaminant concentration levels below acceptable criteria.

- **Safe Handling**

Inhalation: Avoid prolonged or repeated breathing of vapor.

Skin: Avoid prolonged or repeated contact with skin.

Eyes: Avoid prolonged or repeated contact with eyes.

Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary exposure and removal of the material from eyes, skin and clothing. Wash hands thoroughly after handling.

Section Seven--Spill or Leak and Disposal Procedures

- **Spill or leak**

Large quantities: Enclose with diking material to prevent seepage into natural bodies of water, then consult Custom-Pak Adhesives.

Small quantities: Soak up with absorbent material and remove to chemical disposal area.

- **Disposal**

Recover free liquid. Absorb residue and dispose of according to local, state/provincial, and federal requirements.

Section Eight--Storage

- Keep from freezing.
- Do not store near strong oxidizing chemicals.
- Store in a tightly closed container.



Custom Work Deserves a Custom Bond

Section Nine--Transportation

Refer to bill of lading for proper DOT description.

Section Ten--Reactivity Data

- Normally stable as defined in NFPA 704-12(4-3.1).
- Hazardous polymerization: Will not occur.
- Incompatibilities: Oxidizers, acids or bases.
- Decomposition products may include: Oxides of carbon.

Section Eleven--Regulatory and other information

The OSHA Hazard Communication Standard 29 CFR 1910.1200 requires that the information contained on these sheets be made available to your workers. Instruct your workers to handle this product properly.

SARA TITLE III SECTION 313
AND 40 CFR PART 372
TOXIC CHEMICAL NOTIFICATION SHEET

MPA FAST

This product contains **NO** toxic chemical(s) subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986, and Subpart C-Supplier Notification Requirement of 40 CFR Part 372.

This Toxic Chemical Notification Sheet must not be detached from the MSDS. Any copying and redistribution of the MSDS shall include copying and redistribution of this notification sheet attached to copies of the MSDS subsequently redistributed.