

TECHNICAL DATA SHEET

WATER-BASED WOOD FILLER

PRODUCT DESCRIPTION

FAMOWOOD, the #1 choice of woodworking professionals for over 50 years, has developed a new water-soluble formula certified by Scientific Certification Systems as having no smog producing ingredients. Whether you're masking small or large defects, FAMOWOOD can be used inside or outside and takes stains and paint evenly, making it ideal for any custom project. FAMOWOOD spreads evenly into cracks and holes without shrinking, crumbling or cracking. In addition, Famowood requires very little sanding to achieve a desired finished look.

PRODUCT CHARACTERISTICS & BENEFITS

High solid content	Saw, drill, sand, plane & nail, just like real wood
Easy application	Spreads evenly into cracks & holes without crumbling or cracking
Fast dry time	Can be used indoors and outdoors
Superior strength	Hard finish with little or no shrinkage
Quality finish	Accepts stains and paints evenly with minimal sanding

PHYSICAL CHARACTERISTICS

Solids	82% ± 2.0% (by weight)
Density	15.0 - 16.0 lbs/gal
Colors	Natural, Red Oak, Oak, Walnut, White Pine, Fir/Maple, and more. (Call technical support for other available colors.)
Shelf life	1 ½ years
Storage	Store between 45°F (7°C) and 85°F (29°C)
Freeze/thaw stability	stable up to three to five freezes; allow product to warm to room temperature before using.

DIRECTIONS FOR USE

1. For best adhesion, cracks or defects should be clean and dry.
2. Press firmly into defect with gun, by hand, or with putty knife.
3. A thin film will dry within minutes. Lower temperatures require longer drying periods.
4. When dry, sand flush with surrounding surfaces.
5. Surfaces may be painted, varnished, lacquered, waxed, or shellacked.
6. Famowood can be drilled, nailed, planed, or sawed like ordinary wood.
7. Clean tools while still wet with water or soap with water. If product has dried on tools, use chlorinated solvent or steam.
8. Close container after each use.

HAZARDS

Before working with this product, read and become familiar with information concerning hazards, proper use and handling.
For an MSDS, visit www.tech@eclecticproducts.com or call (800) 333-9826.

LIMITED WARRANTY

The product is warranted against any defect in materials or workmanship under normal use and service for a period of 180 days after the date of purchase. The product is also warranted under any implied warranties provided under applicable state law, including, without limitation, the implied warranty of merchantability and the implied warranty of fitness for a particular purpose, for a period of 180 days after the date of purchase. This warranty covers only the original buyer of the product. For warranty service, the buyer should contact the store where the product was purchased, or write Eclectic Products, Inc. P.O. Box 4450, Pineville, LA 71360 or call (800) 767-4667. This warranty gives you specific legal rights, and you also have other rights, which vary from state to state.

TECHNICAL DATA SHEET **WATER-BASED WOOD FILLER**

WOOD FILLER COMPARISON TEST

Five comprehensive tests

- Dry time
- Shrinkage
- Adhesion
- Stainability
- Sanding

Results

FAMOWOOD WATER-BASED WOOD FILLER came out on top for overall superiority.

Average of Total Test Scores

